



- Higher reliability from integrated design principle
- Performing well at wide temperature range
- Reasonable size and light weight
- Meet ETSI, FCC Standards

GeoSat 50W Ku-Band Block Up-Converter (BUC)

Model: GBE50KU3



Section	Item	Specification
Power Requirement	RF Frequency	13.75-14.5 GHz
	IF Frequency	950-1700 MHz
Input Characteristics	External Reference	10 MHz, 0±5 dBm
	Saturated Output Power	47.5 dBm
	Rated Output Power	47 dBm
	P1dB Output Power	NA
	IMD3 @3dB back-off from Rated Output Power	≤ -25 dBc
Output Characteristics	Small Signal Gain	70 dB
	Gain Variation	1 dB p-p/ 36 MHz
		3 dB p-p/ 500 MHz
		4 dB p-p/ 750 MHz
	Gain Stability	±1.5 dB
Gain Adjustment Range	20 dB (Step: 0.1 dB)	
Transfer Characteristics	Phase Noise (IES-308/309)	≤ -63 dBc/Hz @100 Hz
		≤ -73 dBc/Hz @1 KHz
		≤ -83 dBc/Hz @10 KHz
		≤ -93 dBc/Hz @100 KHz
	Output Spurious	-55 dBc (max)
Power Supply	85 to 265 VAC	
Power Supply Draw @Rated Output Power	420W	

Continued on the next page ▼

Section	Item	Specification
	RF Output Connector	WR75-G (Grooved)
	RF Output VSWR	1.25:1
	IF Input Connector	N-Type Female
	IF Input VSWR	1.5:1
	Power Supply Connector	ACS02E-14S-7P
	M & C Connector	PT02E-14-19P RS-485, RS-232 & Ethernet
	LED Indicators	LEDs off: Equipment function properly Yellow: PLL unlock alarm
	Size	206*136*136 mm
	Weight	5 Kg
	Operating Temperature	-40 to +60 °C
	Humidity	0-100% (Condensing)
	Altitude	0-10000 F ASL

www.geosatmicrowave.com

sales@geosatmicrowave.com