

U350 Series L-band Upconverters

INPUT SPECIFICATION		Options
1. Frequency range:	70 ± 20MHz or 140 ± 40MHz (check model table)	
2. Connector:	BNC	TNC
3. Impedance:	50Ω	75Ω
4. Return loss:	≥15dB	≥20dB (*)
OUTPUT SPECIFICATION		
5. Frequency range:	950 to 2,150MHz (check model table)	
6. Connector:	N-type	SMA
7. Impedance:	50Ω	
8. Return loss:	≥15dB	
9. 1dB compression point:	+10dBm	
10. Third order intercept:	+20dBm	
TRANSFER CHARACTERISTICS		
11. Gain:	0 to 30dB, adjustable in 0.1dB steps	
12. Gain ripple:	over ±20MHz: ≤1dB p.t.p.	
	over input band: ≤3dB p.t.p	
13. Group delay distortion:	over ±5MHz <2ns	
	over ±20MHz <5ns	
14. Gain stability, 0°C to 50°C:	±1dB	
15. Frequency stability, 0°C to 50°C:	2 x 10 ⁻⁷	Option 1: 10 ⁻⁷ Option 2: 10 ⁻⁸ Option 3: 3 x 10 ⁻⁹
16. External reference:	10MHz, 0dBm	5MHz, 0dBm
17. Synthesiser step size:	1kHz	
18. Noise figure (full gain):	<15dB	
Spurii		
19. Image rejection:	>75dB	
20. In-band spurii (at 0dBm output):	<-60dBc	
PHASE NOISE		
21. 10Hz:	<-60dBc/Hz	
22. 100Hz:	<-75dBc/Hz	
23. 1kHz:	<-80dBc/Hz	
24. 10kHz:	<-85dBc/Hz	
25. 100kHz:	<-95dBc/Hz	
26. 1MHz:	<-110dBc/Hz	
27. Mains related:	<-60dBc	
MISCELLANEOUS		
28. Power supply:	115V/230V ±10% 50/60Hz ±10%, 30VA	
29. Mechanical:	1U 19" frame, 400mm deep	
30. Temperature:	Operating: 0° to 50°C	
	Storage: -40° to 85°C	
31. Relative humidity:	Operating: 0 to 90%	
	Storage: 0 to 95%	
32. Summary alarm:	NO and NC dry relay contacts via rear mounted connector	
33. Summary alarm indication:	Front panel LED	
34. Remote control:	RS232/RS485 serial interface	

(*) Noise figure increases by 3dB, overall gain decreases by 3dB.

MODEL TABLE

Output Frequency	Input frequency and bandwidth		
	70 ± 20MHz	140 ± 40MHz	70 ± 20MHz, 140 ± 20MHz and ±40MHz
950 - 1,750MHz	U350	U355	U370
950 - 2,150MHz	U351	U356	U371